



R&F Technology Co., Ltd

C9 Smart EFT POS



FHD IPS Touch screen

1920x1080 resolution
350 nits High Brightness
85° Wide Viewing Angle



Ultra-Thin That Surprises

The screen thickness is 16mm and the thinnest part is 8.75mm 170%
Screen-to-body ratio



Modular for Ultimate Flexibility

Experience seamless integration with different functional components



Built-in NFC

Tap on the customer display to support softPos



More Display options



Singke Display



15.6" + 10."



15.6" + 15.6"



Telpo Os
(Based on Android 14)



Octa-Core



4GB+64GB



2.4GHz+5GHz



Rich Interface



Telpo MDM

Specifications

Processor	Octa-Core 2.2GHz	Interfaces	4 USB,1RJII(RS232),1 RJ12 1 RJ45 I DC Port 1 TYPE C(Debug use). 1 TYPE C(HUB) ※ 2 Micro UsB (10.1" ScreenExtended Port)
OS	Android 14		
Memory	4GB RAM, 64GB ROM ※ 8GB RAM. 128GB ROM ※ 8GB RAM, 256GB ROM	Keypad	1 Power Key
Display	15.6",1920*1080, support touch, G+G	Power supply	12V/3A
Customer Display	10.1",1280*800, support touch, G+G	WLAN	802. a/b/g/n/ac (2.4GHz/5GHz)
	15.6".1920*1080, support touch,G+G	Bluetooth	Bluetooth 5.0, support Classic & BLE
Financial Card Reader	NFC: ISO14443 Type A/B, Mifare, EMVContactless LL, Paywave,Paypass Smart Card: is07816 (Install on 10.1" screen side)	Ethernet	10/100/1000Mbps
Contactless Card Reader	IsO14443 Type A/B, Mifare (Under the 10.1 display)	Operating Temperature	-10°C~45°C
※ Fingerprint Button	Support	Storage Temperature	-25°C~60°C
Camera	1 Speaker 3w ※ 2 Microphone	Humidity	5%RH~95%RH, Non-condensing
		※ Certification	CE. FCC, BIS ※ GMS

※optional Datasheet may be revised or amended by product specs.

APPLICATION



Restaurant



Supermarket



Hotel

